

6.5" Two-Way In-Wall Loudspeaker



R-3650-W

The Klipsch R-3650-W in-wall loudspeaker offers a sophisticated, yet uncomplicated listening experience. Whether used for home theater or stereo music applications, this high-performance and installer-friendly model will forever change the way you integrate sound into your life.

Featuring a 6.5-inch copper-colored IMG woofer, a 1-inch aluminum tweeter, exclusive Tractrix® Horn technology, as well as a treble contour switch, this affordable and dynamic in-wall speaker gives you plenty of bang for your buck.

Available in a white finish, the R-3650-W can be paired with one of Klipsch's new installation kits (sold separately). Each of these revolutionary kit designs allow for increased mounting flexibility and incorporate a mud ring, wire tie and universal metal mesh wing for multi-position placement and a color-coded bracket for easy speaker size identification.

- High sensitivity and power handling
- Pivoting Tractrix Horn compression driver tweeter for clear sound in any location
- Treble attenuation switch and IR receiver knock out
- Single piece grille frame and rustproof aluminum grille

SPECIFICATIONS

FREQUENCY RESPONSE	60Hz-20kHz \pm 3dB
SENSITIVITY	92dB @ 1 watt/1 meter
NOMINAL IMPEDANCE	8 ohms
CROSSOVER FREQUENCY	2200Hz
POWER HANDLING	50 watts (200 watts peak)
ENCLOSURE MATERIAL/TYPE	ABS, Infinite baffle, front flush with wall
DRIVE COMPONENTS	Two-way system using one 1" (2.54cm) Aluminum dome compression tweeter with a 6" (15.24cm) square 90° x 60° pivoting Tractrix® Horn and one 6.5" (16.51cm) IMG woofer
WIRE GAUGE ACCOMMODATED	12
WEIGHT	7.2 lbs. (3.25kg)
HEIGHT	14.3" (36.32cm)
WIDTH	9.3" (23.62cm)
MOUNTING DEPTH	3.75" (9.5cm)
CUT OUT DIMENSIONS	13" (33.02cm) x 8" (20.32cm)
FINISH	White
INSTALLATION KIT	IK-650-W (sold separately)

www.klipsch.com
1-800-KLIPSCH

